

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

100.000 Renia - MULTI-Colle Multi Purpose Adhesive tfx

Print date: 13.09.2015

Product code: 100.000Xylene

Page 1 of 15

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

100.000 Renia - MULTI-Colle Multi Purpose Adhesive tfx

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**

Adhesives, sealants

Roller application or brushing of adhesive and other coating.

1.3. Details of the supplier of the safety data sheet

Company name:	Renia Gesellschaft mbH. Chemische Fabrik	
	D	
Street:	Ostmerheimer Straße 516	
Place:	D-51109 Köln (Cologne)	
Post-office box:	910659	
	D-51076 Köln (Cologne)	
Telephone:	+49-221-630799-0	Telefax: +49-221-630700-50
e-mail:	info@renia.com	
Contact person:	Heinz Buchholz Dipl.Chem	Telephone: 16
e-mail:	labor@renia.com	
Internet:	www.renia.com	
Responsible Department:	Labor 07:30 - 16:00 Uhr	

1.4. Emergency telephone number: +49-221-630799-0**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****Regulation (EC) No. 1272/2008**

Hazard categories:

Flammable liquid: Flam. Liq. 2

Skin corrosion/irritation: Skin Irrit. 2

Serious eye damage/eye irritation: Eye Irrit. 2

Respiratory or skin sensitisation: Skin Sens. 1

Specific target organ toxicity - single exposure: STOT SE 3

Hazardous to the aquatic environment: Aquatic Chronic 2

Hazard Statements:

Highly flammable liquid and vapour.

Causes skin irritation.

May cause an allergic skin reaction.

Causes serious eye irritation.

May cause drowsiness or dizziness.

Toxic to aquatic life with long lasting effects.

2.2. Label elements**Regulation (EC) No. 1272/2008****Hazardous components which must be listed on the label**

ethyl acetate

methyl 2-methylprop-2-enoate, methyl 2-methylpropenoate, methyl methacrylate

Rosin, colophony

Signal word: Danger

Safety Data Sheet

according to Regulation (EC) No 1907/2006

100.000 Renia - MULTI-Colle Multi Purpose Adhesive tfx

Print date: 13.09.2015

Product code: 100.000Xylene

Page 2 of 15

Pictograms:



Hazard statements

H225	Highly flammable liquid and vapour.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.

Precautionary statements

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233	Keep container tightly closed.
P235	Keep cool.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P264	Wash Protective clothing. thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P272	Contaminated work clothing should not be allowed out of the workplace.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312	Call a POISON CENTER/doctor if you feel unwell.
P321	Specific treatment (see ... on this label).
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P337+P313	If eye irritation persists: Get medical advice/attention.
P352	Wash with plenty of water.
P364	And wash it before reuse.
P370+P378	In case of fire: Use alcohol resistant foam to extinguish.
P391	Collect spillage.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P405	Store locked up.
P501	Dispose of contents/container to Waste management.

Special labelling of certain mixtures

EUH018	In use may form flammable/explosive vapour-air mixture.
EUH066	Repeated exposure may cause skin dryness or cracking.

Additional advice on labelling

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

100.000 Renia - MULTI-Colle Multi Purpose Adhesive tfx

Print date: 13.09.2015

Product code: 100.000Xylene

Page 3 of 15

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients**3.2. Mixtures****Chemical characterization**

grafted polychloroprene adhesive with modified synthetic resins and stabilizers in a mixture of organic solvents

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification according to Regulation (EC) No. 1272/2008 [CLP]			
141-78-6	ethyl acetate			35 - < 40 %
	205-500-4	607-022-00-5	01-2119475103-46	
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 EUH066			
64742-49-0	Naphtha (petroleum), hydrotreated light; Low boiling point hydrogen treated naphtha			25 - < 30 %
	265-151-9	649-328-00-1	01-2119475514-35	
	Flam. Liq. 2, Skin Irrit. 2, Asp. Tox. 1, Aquatic Chronic 2; H225 H315 H304 H411			
1330-20-7	xylene			10 - < 15 %
	215-535-7	601-022-00-9	01-2119486134	
	Flam. Liq. 3, Acute Tox. 4, Acute Tox. 4, Skin Irrit. 2; H226 H312 H332 H315			
80-62-6	methyl 2-methylprop-2-enoate, methyl 2-methylpropenoate, methyl methacrylate			1 - < 5 %
	201-297-1	607-035-00-6	01-2119452498-28	
	Flam. Liq. 2, Skin Irrit. 2, Skin Sens. 1, STOT SE 3; H225 H315 H317 H335			
8052-10-6	Rosin, colophony			< 1 %
	232-484-6	650-015-00-7		
	Skin Sens. 1; H317			

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures**4.1. Description of first aid measures****General information**

Remove affected person from the danger area and lay down.

After inhalation

Provide fresh air. If breathing is irregular or stopped, administer artificial respiration. Medical treatment necessary. In case of inhalation of decomposition products, affected person should be moved into fresh air and kept still. Remove casualty to fresh air and keep warm and at rest.

After contact with skin

After contact with skin, wash immediately with polyethylene glycol, followed by plenty of water. Take off immediately all contaminated clothing and wash it before reuse. Medical treatment necessary. Remove contaminated, saturated clothing immediately. After contact with skin, wash immediately with plenty of water and soap. Grease skin after contact.

After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately. In case of contact with eyes, rinse immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Subsequently consult an ophthalmologist.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

100.000 Renia - MULTI-Colle Multi Purpose Adhesive tfx

Print date: 13.09.2015

Product code: 100.000Xylene

Page 4 of 15

After ingestion

Rinse mouth immediately and drink plenty of water. Do NOT induce vomiting. In case of allergic symptoms, especially in the breathing area, seek medical advice immediately.

4.2. Most important symptoms and effects, both acute and delayed

Allergic reactions.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically. Position and transport victim on their side. In case of respiratory distress, bring into semi-upright, seated position. Where appropriate artificial ventilation.

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

Carbon dioxide (CO₂), Foam, Extinguishing powder, alcohol resistant foam, ABC powder, Atomized water, Dry sand.

Unsuitable extinguishing media

Water, High power water jet, High power water jet.

5.2. Special hazards arising from the substance or mixture

Flammable. Vapours can form explosive mixtures with air. In case of fire and/or explosion do not breathe fumes. In case of fire may be liberated: Hydrogen chloride (HCl). Burning produces heavy smoke.

5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing. Full protection suit. Special exposure hazards arising from the substance itself, combustion products, resulting gases: In case of fire: Wear self-contained breathing apparatus.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water. Use water spray jet to protect personnel and to cool endangered containers. Contaminated fire-fighting water must be collected separately. Remove product from area of fire. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Remove all sources of ignition. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment. Remove all sources of ignition. Provide adequate ventilation.

6.2. Environmental precautions

Do not allow uncontrolled discharge of product into the environment. Danger of explosion Do not allow to enter into surface water or drains. Cover drains.

6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal. Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Collect in closed containers for disposal.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage**7.1. Precautions for safe handling**

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

100.000 Renia - MULTI-Colle Multi Purpose Adhesive tfx

Print date: 13.09.2015

Product code: 100.000Xylene

Page 5 of 15

Advice on safe handling

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray. If handled uncovered, arrangements with local exhaust ventilation should be used if possible. If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

Advice on protection against fire and explosion

Keep away from sources of ignition. - No smoking. Take precautionary measures against static discharges. Vapours can form explosive mixtures with air. Keep away from sources of ignition. - No smoking. Only use the material in places where open light, fire and other flammable sources can be kept away. Vapours / aerosols must be extracted by suction immediately at point of origin.

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

Keep container tightly closed. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep only in the original container in a cool, well-ventilated place. Keep container tightly closed. Recommended storage temperature: 15-30 °C Ensure adequate ventilation of the storage area.

Advice on storage compatibility

Do not store together with: Oxidising agent. Pyrophoric or self-heating substances. Store packaging and combustible materials separately from one another. Keep away from food, drink and animal feedingstuffs.

Further information on storage conditions

Floors should be impervious, resistant to liquids and easy to clean.
Store small packages in a suitable, robust cabinet.

7.3. Specific end use(s)

Adhesives, sealants Roller application or brushing of adhesive and other coating.

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
141-78-6	Ethyl acetate	200	-		TWA (8 h)	WEL
		400	-		STEL (15 min)	WEL
80-62-6	Methyl methacrylate	50	208		TWA (8 h)	WEL
		100	416		STEL (15 min)	WEL
1330-20-7	Xylene: mixed isomers	50	220		TWA (8 h)	WEL
		100	441		STEL (15 min)	WEL

Biological Monitoring Guidance Values (EH40)

CAS No	Substance	Parameter	Value	Test material	Sampling time
1330-20-7	Xylene, o-, m-, p- or mixed isomers	methyl hippuric acid	650 mmol/mol	urine	Post shift

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

100.000 Renia - MULTI-Colle Multi Purpose Adhesive tfx

Print date: 13.09.2015

Product code: 100.000Xylene

Page 6 of 15

DNEL/DMEL values

CAS No	Substance			
DNEL type		Exposure route	Effect	Value
141-78-6	ethyl acetate			
Worker DNEL, long-term		inhalation	systemic	1468 mg/m ³
Worker DNEL, acute		inhalation	local	1468 mg/m ³
Worker DNEL, long-term		dermal	systemic	63 mg/kg bw/day
Worker DNEL, long-term		inhalation	local	734 mg/m ³
Consumer DNEL, acute		inhalation	systemic	734 mg/m ³
Consumer DNEL, long-term		inhalation	local	734 mg/m ³
Consumer DNEL, long-term		dermal	systemic	37 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	367 mg/m ³
Consumer DNEL, long-term		oral	systemic	4,5 mg/kg bw/day
Consumer DNEL, acute		inhalation	local	367 mg/m ³
64742-49-0	Naphtha (petroleum), hydrotreated light; Low boiling point hydrogen treated naphtha			
Worker DNEL, long-term		dermal	systemic	13964 mg/kg bw/day
Worker DNEL, long-term		inhalation	systemic	5306 mg/m ³
Consumer DNEL, long-term		dermal	systemic	1377 mg/kg bw/day
Consumer DNEL, long-term		inhalation	local	1137 mg/m ³
Consumer DNEL, long-term		oral	systemic	1601 mg/kg bw/day
1330-20-7	xylene			
Consumer DNEL, long-term		oral	systemic	1,6 mg/kg bw/day
Consumer DNEL, long-term		dermal	systemic	108 mg/kg bw/day
Worker DNEL, long-term		dermal	systemic	180 mg/kg bw/day
Consumer DNEL, acute		inhalation	local	174 mg/m ³
Worker DNEL, acute		inhalation	local	289 mg/m ³
Consumer DNEL, long-term		inhalation	systemic	14,8 mg/m ³
Worker DNEL, long-term		inhalation	systemic	77 mg/m ³
80-62-6	methyl 2-methylprop-2-enoate, methyl 2-methylpropenoate, methyl methacrylate			
Worker DNEL, long-term		inhalation	systemic	210 mg/m ³
Worker DNEL, long-term		dermal	systemic	13,67 mg/kg bw/day

Safety Data Sheet

according to Regulation (EC) No 1907/2006

100.000 Renia - MULTI-Colle Multi Purpose Adhesive tfx

Print date: 13.09.2015

Product code: 100.000Xylene

Page 7 of 15

PNEC values

CAS No	Substance	
Environmental compartment		Value
141-78-6	ethyl acetate	
Freshwater		0,26 mg/l
Marine water		0,026 mg/l
Freshwater sediment		0,34 mg/kg
Marine sediment		0,034 mg/kg
Soil		0,22 mg/kg
1330-20-7	xylene	
Freshwater		0,327 mg/l
Freshwater (intermittent releases)		0,327 mg/l
Marine water		0,327 mg/l
Freshwater sediment		12,46 mg/kg
Marine sediment		12,46 mg/kg
Soil		2,31 mg/kg
Micro-organisms in sewage treatment plants (STP)		6,58 mg/l
80-62-6	methyl 2-methylprop-2-enoate, methyl 2-methylpropenoate, methyl methacrylate	
Freshwater		0,94 mg/l

8.2. Exposure controls



Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Protective and hygiene measures

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme.

Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink. Do not eat, drink, smoke or sneeze at the workplace. Wash hands before breaks and after work. Before starting work, apply solvent-resistant skincare preparations.

Eye/face protection

Suitable eye protection: goggles.

Hand protection

Test suitability of gloves before use.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Suitable material: Butyl caoutchouc (butyl rubber)

Thickness of the glove material : 0,5 mm

Breakthrough time (maximum wearing time) : >= 1 h

Skin protection

When handling with chemical substances, protective clothing with CE-labels including the four control digits must be worn.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

100.000 Renia - MULTI-Colle Multi Purpose Adhesive tfx

Print date: 13.09.2015

Product code: 100.000Xylene

Page 8 of 15

Respiratory protection

Respiratory protection necessary at: insufficient ventilation. With correct and proper use, and under normal conditions, breathing protection is not required. If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn. Combination filtering device (EN 14387) Use the following filter types for cleaning waste gases: A-P2

Environmental exposure controls

Do not allow to enter into soil/subsoil. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state:	liquid
Colour:	light yellow
Odour:	ester

Test method

pH-Value:	Test not required.
-----------	--------------------

Changes in the physical state

Melting point:	not determined
Initial boiling point and boiling range:	65 °C DIN 53 171
Flash point:	-16 °C DIN 51 755

Flammability

Solid:	not applicable
Gas:	not applicable
Lower explosion limits:	1 vol. %
Upper explosion limits:	11,5 vol. %
Ignition temperature:	200 °C DIN 51 794

Auto-ignition temperature

Solid:	not applicable
Gas:	not applicable
Decomposition temperature:	not determined

Oxidizing properties

Not oxidizing.

Vapour pressure:	175 hPa DIN EN 12
(at 20 °C)	
Vapour pressure:	950 hPa
(at 50 °C)	
Density (at 20 °C):	0,84 g/cm ³ DIN 51 757
Water solubility:	insoluble

Solubility in other solvents

not determined

Partition coefficient:	not determined
Viscosity / dynamic:	1200-2000 mPa·s DIN 51550
(at 20 °C)	
Flow time:	> 300 (3 mm)
(at 20 °C)	

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

100.000 Renia - MULTI-Colle Multi Purpose Adhesive tfx

Print date: 13.09.2015

Product code: 100.000Xylene

Page 9 of 15

Vapour density:	not determined
Evaporation rate:	not determined
Solvent separation test:	< 0,1 %
Solvent content:	81,00 %

9.2. Other information

Solid content:	19,00 %
----------------	---------

SECTION 10: Stability and reactivity**10.1. Reactivity**

Flammable, Ignition hazard. Explosive. The study does not need to be conducted because the substance is known to be stable at room temperature for prolonged periods of time (days).

10.2. Chemical stability

The study does not need to be conducted because the substance is known to be stable at room temperature for prolonged periods of time (days).

10.3. Possibility of hazardous reactions

Gas/vapour, highly flammable.

10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air. Risk of explosion by shock, friction, fire or other sources of ignition. Remove all sources of ignition. Keep away from heat. Ignition hazard. Decomposition takes place from temperatures above: > 150 °C

10.5. Incompatible materials

Protect against: Contact with air/oxygen. Acid, concentrated. , Oxidizing agents, strong.

10.6. Hazardous decomposition products

Thermal decomposition can lead to the escape of irritating gases and vapours.

SECTION 11: Toxicological information**11.1. Information on toxicological effects****Toxicokinetics, metabolism and distribution**

There are no data available on the preparation/mixture itself.

Acute toxicity

Based on available data, the classification criteria are not met.

There are no data available on the preparation/mixture itself.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

100.000 Renia - MULTI-Colle Multi Purpose Adhesive tfx

Print date: 13.09.2015

Product code: 100.000Xylene

Page 10 of 15

CAS No	Chemical name				
	Exposure routes	Method	Dose	Species	Source
141-78-6	ethyl acetate				
	oral	LD50	5600 mg/kg	Rat	
	dermal	LD50	18000 mg/kg	Rabbit	
	inhalative (4 h) vapour	LC50	58 mg/l	Rat	
64742-49-0	Naphtha (petroleum), hydrotreated light; Low boiling point hydrogen treated naphtha				
	oral	LD50	5000 mg/kg	Rat	
	dermal	LD50	3160 mg/kg	Rabbit	
	inhalative (4 h) vapour	LC50	25 mg/l	Rat	
1330-20-7	xylene				
	oral	LD50	8700 mg/kg	Rat	
	dermal	LD50	2000 mg/kg	Rabbit	
	inhalative (4 h) vapour	LC50	6350 mg/l	Rat	
	inhalative aerosol	ATE	1,5 mg/l		
80-62-6	methyl 2-methylprop-2-enoate, methyl 2-methylpropenoate, methyl methacrylate				
	oral	LD50	5000 mg/kg	Rat	
	dermal	LD50	5000 mg/kg	Rabbit	
	inhalative (4 h) vapour	LC50	29,8 mg/l	Rat	
8052-10-6	Rosin, colophony				
	oral	LD50	2000 mg/kg	Rat	
	dermal	LD50	2000 mg/kg	Rabbit	

Irritation and corrosivity

Causes skin irritation.

Causes serious eye irritation.

Frequently or prolonged contact with skin may cause dermal irritation.

Sensitising effects

May cause an allergic skin reaction. (methyl 2-methylprop-2-enoate, methyl 2-methylpropenoate, methyl methacrylate), (Rosin, colophony)

May cause sensitization by inhalation and skin contact. Kolophonium, MMA

STOT-single exposure

May cause drowsiness or dizziness. (ethyl acetate)

Severe effects after repeated or prolonged exposure

Repeated exposure may cause skin dryness or cracking.

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Inhalation causes narcotic effects/intoxication.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

There are no data available on the preparation/mixture itself.

Aspiration hazard

Based on available data, the classification criteria are not met.

Specific effects in experiment on an animal

There are no data available on the preparation/mixture itself.

Additional information on tests

This mixture is classified as hazardous according to regulation (EC) No. 1272/2008 [CLP].

Safety Data Sheet

according to Regulation (EC) No 1907/2006

100.000 Renia - MULTI-Colle Multi Purpose Adhesive tfx

Print date: 13.09.2015

Product code: 100.000Xylene

Page 11 of 15

SECTION 12: Ecological information

12.1. Toxicity

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Longterm fish toxicity Product is easily volatile. Product is slightly soluble in test vehicle. An aqueous dispersion has been tested.

CAS No	Chemical name					
	Aquatic toxicity	Method	Dose	[h] [d]	Species	Source
141-78-6	ethyl acetate					
	Acute fish toxicity	LC50	230 mg/l	96 h	Pimephales promelas	
	Acute algae toxicity	ErC50	3300 mg/l	72 h	Scenedesmus subspicatus	
	Acute crustacea toxicity	EC50	717 mg/l	48 h	Daphnia magna	
64742-49-0	Naphtha (petroleum), hydrotreated light; Low boiling point hydrogen treated naphtha					
	Acute fish toxicity	LC50	10 mg/l	96 h	Fisch	
	Acute algae toxicity	ErC50	10 mg/l	72 h	Alge	
	Acute crustacea toxicity	EC50	10 mg/l	48 h	Daphnie	
1330-20-7	xylene					
	Acute fish toxicity	LC50	26 mg/l	96 h	Pimephales promelas	
	Acute algae toxicity	ErC50	4 mg/l	72 h	Pseudokirchneriella subcapitata	
	Acute crustacea toxicity	EC50	165 mg/l	48 h		
80-62-6	methyl 2-methylprop-2-enoate, methyl 2-methylpropenoate, methyl methacrylate					
	Acute fish toxicity	LC50	80 mg/l	96 h	oncorhynchus mykiss	
	Acute algae toxicity	ErC50	110 mg/l	72 h	Selenastrum capricornutum	
	Acute crustacea toxicity	EC50	69 mg/l	48 h	Daphnia Magna	
	Fish toxicity	NOEC	9,4 mg/l			

12.2. Persistence and degradability

The product has not been tested. Product is biodegradable with difficulty.

12.3. Bioaccumulative potential

There are no data available on the preparation/mixture itself.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
141-78-6	ethyl acetate	0,6
64742-49-0	Naphtha (petroleum), hydrotreated light; Low boiling point hydrogen treated naphtha	4-5
1330-20-7	xylene	3
80-62-6	methyl 2-methylprop-2-enoate, methyl 2-methylpropenoate, methyl methacrylate	1,38

BCF

CAS No	Chemical name	BCF	Species	Source
141-78-6	ethyl acetate	30		

12.4. Mobility in soil

There are no data available on the preparation/mixture itself.

12.5. Results of PBT and vPvB assessment

There are no data available on the preparation/mixture itself.

12.6. Other adverse effects

Toxic to aquatic life with long lasting effects.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

100.000 Renia - MULTI-Colle Multi Purpose Adhesive tfx

Print date: 13.09.2015

Product code: 100.000Xylene

Page 12 of 15

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Do not let product enter drains.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Advice on disposal

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Dispose of waste according to applicable legislation. Consult the appropriate local waste disposal expert about waste disposal.

Waste disposal number of waste from residues/unused products

080406 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products)

Waste disposal number of used product

080406 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products)

Waste disposal number of contaminated packaging

150104 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); metallic packaging

Contaminated packaging

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself. Completely emptied packages can be recycled.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number:	UN 1133
14.2. UN proper shipping name:	Adhesives
14.3. Transport hazard class(es):	3
14.4. Packing group:	III
Hazard label:	3



Classification code:	F1
Limited quantity:	5 L
Excepted quantity:	E1
Transport category:	3
Hazard No:	33
Tunnel restriction code:	D/E

Other applicable information (land transport)

Additional information on classification 2.2.3.1.4 GGVSEB

Inland waterways transport (ADN)

14.1. UN number:	UN 1133
14.2. UN proper shipping name:	Adhesives
14.3. Transport hazard class(es):	3
14.4. Packing group:	III

Safety Data Sheet

according to Regulation (EC) No 1907/2006

100.000 Renia - MULTI-Colle Multi Purpose Adhesive tfx

Print date: 13.09.2015

Product code: 100.000Xylene

Page 13 of 15

Hazard label: 3



Classification code: F1
 Limited quantity: 5 L
 Excepted quantity: E1

Other applicable information (inland waterways transport)

Additional information on classification : 2.2.3.1.4 ADR / GGVSEB

Marine transport (IMDG)

14.1. UN number: UN 1133
14.2. UN proper shipping name: Adhesives
14.3. Transport hazard class(es): 3
14.4. Packing group: III
 Hazard label: 3



Special Provisions: 223, 955
 Limited quantity: 5 L
 Excepted quantity: E1
 EmS: F-E, S-D
 Segregation group: acids

Other applicable information (marine transport)

Category: A

Additional information on classification : 2.2.3 IMO/GGVSee

Air transport (ICAO)

14.1. UN number: UN 1133
14.2. UN proper shipping name: Adhesives
14.3. Transport hazard class(es): 3
14.4. Packing group: III
 Hazard label: 3



Special Provisions: A3
 Limited quantity Passenger: 10 L
 Passenger LQ: Y344
 Excepted quantity: E1
 IATA-packing instructions - Passenger: 355
 IATA-max. quantity - Passenger: 60 L
 IATA-packing instructions - Cargo: 366
 IATA-max. quantity - Cargo: 220 L

Other applicable information (air transport)

220 L

Special provisions: A3

14.5. Environmental hazards

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

100.000 Renia - MULTI-Colle Multi Purpose Adhesive tfx

Print date: 13.09.2015

Product code: 100.000Xylene

Page 14 of 15

ENVIRONMENTALLY HAZARDOUS: yes

**14.6. Special precautions for user**

Warning: Combustible liquid.

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

not applicable

Other applicable information

Additional information on classification 2.2.3.1.4 GGVSEB

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

2010/75/EU (VOC): 100 % (840 g/l)

2004/42/EC (VOC): 100 % (840 g/l)

Additional information

To follow: 850/2004/EC, 79/117/EEC, 689/2008/EC

National regulatory information

Employment restrictions: Observe employment restrictions for young people.

Water contaminating class (D): 2 - water contaminating

Skin resorption/Sensitization: Causes allergic hypersensitivity reactions.

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information**Changes**

This data sheet contains changes from the previous version in section(s): 2.

Abbreviations and acronymsADR: Accord européen sur le transport des marchandises dangereuses par Route
(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service

LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

Relevant H and EUH statements (number and full text)

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

100.000 Renia - MULTI-Colle Multi Purpose Adhesive tfx

Print date: 13.09.2015

Product code: 100.000Xylene

Page 15 of 15

H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.
EUH018	In use may form flammable/explosive vapour-air mixture.
EUH066	Repeated exposure may cause skin dryness or cracking.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)